

FlashTech 723

Airport Acquisition Beacon.

Applications

Identifies airport location.

The FlashTech 723 provides omnidirectional flashes of white light. These distinctive flashes alert pilots to the general vicinity of the airport. The design featuring "no moving parts" keeps the cost of installation, operation and maintenance to a minimum.

Maintenance

An extensive instruction manual and drawings are provided with each system. Trained maintenance personnel and information on support programs are readily available through Flash Technology's field service engineering department. Training is available through Flash University. Technical support is also available.



Flashhead- FH308

- 12,000 \pm 25% effective candelas (ECD) - day - white
- 6,000 \pm 25% effective candelas (ECD) - twilight - white
- 2,000 \pm 25% effective candelas (ECD) - night - white
- 20 flashes per minute
- 360° horizontal coverage
- 5° vertical beam
- Weight: 17 lbs. (7.7 kg)
- Dimensions (H x W):
17 in. x 18.25 in.
431.8 mm x 463.6 mm
- Aerodynamic wind area: .93 square feet (.0864 square meters)

Power Converter – PC 723

- 120, 208, 240, 480 volt 60 hz, or 230 volt 50 hz, single phase (specify on order)
- 130 watts power consumption
- Status relays with form C contacts

* Indicates an optional component for this product.